



**Specify:**

Series (no-hole design) - U-Groove - Wire Size(µm) - Designation - Shank Style - Tool Length

**Example:**

8236-UG-200-1-A-K

DASH NUMBER	T in./µm	F in./µm	FR & BR in./µm	UGR in./µm	UGD in./µm	W in./µm	VGH in./µm
-100-1	.0098/250	.0051/130	.0024/60	.0024/60	.0014/36	.0098/250	.0400/1016
-125-1	.0118/300	.0059/150	.0030/76	.0030/76	.0017/43	.0118/300	.0400/1016
-125-2	.0128/325	.0068/173	.0030/76	.0030/76	.0017/43	.0118/300	.0400/1016
-125-3	.0138/350	.0078/198	.0030/76	.0030/76	.0017/43	.0118/300	.0400/1016
-125-4	.0148/375	.0088/224	.0030/76	.0030/76	.0017/43	.0118/300	.0400/1016
-150-1	.0138/350	.0068/173	.0035/88	.0035/88	.0021/53	.0138/350	.0400/1016
-175-1	.0157/400	.0075/190	.0041/104	.0041/104	.0024/60	.0157/400	.0400/1016
-200-1	.0177/450	.0083/210	.0047/120	.0047/120	.0028/71	.0197/500	.0400/1016
-250-1	.0217/550	.0098/250	.0059/150	.0059/150	.0035/88	.0217/550	.0600/1524
-300-1	.0256/650	.0114/290	.0071/180	.0071/180	.0047/120	.0236/600	.0600/1524
-350-1	.0299/760	.0134/340	.0083/210	.0083/210	.0055/140	.0276/700	.0600/1524
-400-1	.0339/860	.0150/380	.0094/240	.0094/240	.0063/160	.0315/800	.0600/1524
-450-1	.0390/990	.0177/450	.0106/270	.0106/270	.0071/180	.0354/900	.0600/1524
-500-1	.0433/1100	.0197/500	.0118/300	.0118/300	.0079/200	.0394/1000	.0600/1524

Dimensions in inches unless otherwise specified