



Specify: Series/Wire Feed Angle - Hole Size/Bond Length - Length - Options

Example:

2145-2020-S

2130-1510-3/4-F-TiC

Material:

Tungsten Carbide Standard
 Titanium Carbide Optional
 (Specify "-TiC" in part no.)
 Cermet Tip Optional
 (Specify "-BK CER" in part no.)

Features:

The Maxiguide design encloses and guides the wire to the bond foot, thereby enhancing wire control and bond centering.

DASH NUMBER	H in./ μ m \pm .0002/5	BL in./ μ m \pm .0002/5	W in./ μ m \pm .0002/5	FR in./ μ m \pm .0002/5	BR in./ μ m \pm .0002/5	T 30° in./ μ m \pm .0005/13	T 38° & 45° in./ μ m \pm .0005/13	SUGGESTED WIRE DIAMETER in./ μ m
0.0013 hole uses the same specifications as the 0.0015 hole except for the hole dimension								.0007/18 to .0008/20
*1505	.0015/38	.0005/13	.0025/64	.0005/13	.0005/13	.0100/254	.0080/203	
*1507	.0015/38	.0007/18	.0030/76	.0010/25	.0006/15	.0100/254	.0090/229	
*1507A	.0015/38	.0007/18	.0030/76	.0010/25	.0000/0	.0100/254	.0090/229	
*1510	.0015/38	.0010/25	.0030/76	.0010/25	.0006/15	.0110/279	.0090/229	
*1510A	.0015/38	.0010/25	.0030/76	.0010/25	.0000/0	.0110/279	.0090/229	
1515	.0015/38	.0015/38	.0030/76	.0010/25	.0006/15	.0110/279	.0090/229	
1520	.0015/38	.0020/51	.0030/76	.0010/25	.0006/15	.0120/305	.0100/254	
1525	.0015/38	.0025/64	.0030/76	.0010/25	.0006/15	.0120/305	.0100/254	
1530	.0015/38	.0030/76	.0030/76	.0010/25	.0006/15	.0130/330	.0110/279	
0.0017 hole uses the same specifications as the 0.0015 hole except for the hole dimension								.0008/20 to .0010/25
0.0018 hole uses the same specifications as the 0.0020 hole except for the hole dimension								
*2005	.0020/51	.0005/13	.0040/102	.0005/13	.0005/13	.0120/305	.0100/254	.0010/25
*2007	.0020/51	.0007/18	.0040/102	.0005/13	.0005/13	.0120/305	.0110/279	
*2010	.0020/51	.0010/25	.0040/102	.0010/25	.0006/15	.0130/330	.0110/279	
2020	.0020/51	.0020/51	.0040/102	.0010/25	.0010/25	.0140/356	.0120/305	
2022	.0020/51	.0022/56	.0040/102	.0010/25	.0010/25	.0140/356	.0120/305	
2025	.0020/51	.0025/64	.0040/102	.0010/25	.0010/25	.0150/381	.0130/330	
2030	.0020/51	.0030/76	.0040/102	.0010/25	.0010/25	.0150/381	.0130/330	
2040	.0020/51	.0040/102	.0040/102	.0010/25	.0010/25	.0160/406	.0140/356	
0.0023 hole uses the same specifications as the 0.0025 hole except for the hole dimension								
*2510	.0025/64	.0010/25	.0040/102	.0010/25	.0006/15	.0140/356	.0120/305	
2515	.0025/64	.0015/38	.0040/102	.0010/25	.0010/25	.0140/356	.0130/330	
2520	.0025/64	.0020/51	.0040/102	.0010/25	.0010/25	.0150/381	.0130/330	
2522	.0025/64	.0022/56	.0040/102	.0010/25	.0010/25	.0150/381	.0130/330	
2525	.0025/64	.0025/64	.0040/102	.0010/25	.0010/25	.0150/381	.0140/356	
2530	.0025/64	.0030/76	.0040/102	.0010/25	.0010/25	.0150/381	.0140/356	
2535	.0025/64	.0035/89	.0040/102	.0010/25	.0010/25	.0160/406	.0150/381	
2540	.0025/64	.0040/102	.0040/102	.0010/25	.0010/25	.0160/406	.0150/381	
3015	.0030/76	.0015/38	.0050/127	.0015/38	.0010/25	.0170/432	.0170/432	.0015/38 to .0018/46
3020	.0030/76	.0020/51	.0050/127	.0015/38	.0010/25	.0170/432	.0170/432	
3025	.0030/76	.0025/64	.0050/127	.0015/38	.0010/25	.0180/457	.0180/457	
3030	.0030/76	.0030/76	.0050/127	.0015/38	.0010/25	.0180/457	.0180/457	
3035	.0030/76	.0035/89	.0050/127	.0015/38	.0010/25	.0190/483	.0190/483	
3040	.0030/76	.0040/102	.0050/127	.0015/38	.0010/25	.0190/483	.0190/483	.0020/51
3525	.0035/89	.0025/64	.0050/127	.0015/38	.0010/25	.0210/533	.0180/457	
3530	.0035/89	.0030/76	.0050/127	.0015/38	.0010/25	.0210/533	.0190/483	
3535	.0035/89	.0035/89	.0050/127	.0015/38	.0010/25	.0220/559	.0190/483	
3540	.0035/89	.0040/102	.0050/127	.0015/38	.0010/25	.0220/559	.0200/508	
3545	.0035/89	.0045/114	.0050/127	.0015/38	.0010/25	.0230/584	.0200/508	
3550	.0035/89	.0050/127	.0050/127	.0015/38	.0010/25	.0230/584	.0210/533	.0020/51 to .0025/64
4050	.0040/102	.0050/127	.0060/152	.0015/38	.0010/25	.0260/660	.0220/559	
4540	.0045/114	.0040/102	.0070/178	.0020/51	.0010/25	.0270/686	.0250/635	
4545	.0045/114	.0045/114	.0070/178	.0020/51	.0010/25	.0270/686	.0250/635	.0030/76
5050	.0050/127	.0050/127	.0070/178	.0020/51	.0010/25	.0300/762	.0280/711	.0030/76 to .0035/89

* Flat Face Only

Other part numbers are available

Dimensions in inches unless otherwise specified